

Tuff Lite Stainless-Steel Doors

www.coolcurtain.com | Call (800) 854-5719

Technical Specifications

- 16 gauge thick (.0598 inches).
- 2½ pounds of 304 brushed stainless steel per square foot.
- 3/16" thick acrylic window with gasket comes standard in each door panel.
- Low-maintenance stainless steel auto-closing hinges included.
- Can be mounted with hinges on either left or right door jamb.
- Made in the USA.
- Limited 1-year warranty on parts.
- Doors are prefabricated with standard widths, but custom heights are available up to 84" high.

Single Panel Configuration



One door panel made to fit in your opening size.

Actual Panel Width	Window Size	Opening Width	Opening Height
29¼"	9-3/8"X16-3/8"	30" to 31"	78" to 84"
35¼"	12-3/8"X17-3/8"	36"	78" to 84"

Optional ABS Impact Plates ideal for push carts & heavier traffic areas.



Features:

- Door panels swing 180°.
- Available in single panel and double panel configurations.
- 100% comprised of 304 brushed stainless steel.
- Heavy-duty auto-closing hinges allow doors to open with less than a pound of pressure.
- Stain and scratch resistant.
- Easy to sanitize. No coating to absorb microorganisms.
- Modern, elegant, timeless style.
- ABS Impact plates are available for extra durability.
- Easy to clean and sanitize using stainless steel cleaner and a microfiber cloth.

Double Panel Configuration



Two door panels that split in the middle to add up to your opening

Window Size	Opening Width	Opening Height
(2) 8-3/8"X12-3/8"	36"	78" to 84"
(2) 8-3/8"X12-3/8"	42"	78" to 84"
(2) 8-3/8"X12-3/8"	48"	78" to 84"
(2) 9-3/8"X16-3/8"	60"	78" to 84"
(2) 12-3/8"X17-3/8"	72"	78" to 84"

Galvanized door frames available

